

NEW PRODUCT BULLETIN



A.C. DANDY

CSA CERTIFIED LIGHTING CONTROLLER

ECONOLITE SERIES, MODEL #D-LITE-B

- EEMAC 1 enclosure
- Designed as a lighting controller
- Suitable for indoor use
- Photocell terminals are prewired for easy field connection to remote PEC or BMS
- Contactors are lighting rated for HID, tungsten, fluorescent, etc.
- HOA switch controls for bypass (H) off and automatic modes
- Contactors are 600V
- CSA certified

OPTIONS

- Intermatic Model #ST01C astronomical time



- clock for early shutdown or time day permissive
- Alarm interface for 100% on cycle
- Indicator pilot light for On indication
- If 120V control is not available - 208V, 240V, 480V, or 600V primary fused control transformer
- 30A contactors (maximum 12 pole)
- Second level control
- EEMAC 3R weatherproof design
- 18" High Body

Model #	Max. Volts	Amps	Poles	Voltage Control	Dimensions (") H x W x D
D-LITE-B-1	600	20	4	120	12 x 14 x 4½
D-LITE-B-2	600	20	8	120	12 x 14 x 4½
D-LITE-B-3	600	20	12	120	12 x 14 x 4½
D-LITE-B-4	600	20	16	120	18 x 14 x 4½

For more information visit acdandy.com or call 1.800.642.2952