

NEW PRODUCT BULLETIN



A.C. DANDY

A.C. DANDY POWER SERVICE

Model #PDC-FF

- EEMAC 3R Enclosure
- Specifically designed as a service entrance rated, pad mount, weatherproof power distribution centre complete with CT/PT section and load side terminals
- Ideal for supply of various feeders to multiple locations (as per CEC #14-100)
- Standard load terminals are (8) #6-250 Cu/Al mechanical lugs, (8) #6-250 provisions, & (2) #2-600 provisions per phase + neutral & (8) #10-2/0 & (4) #6-250 ground lugs
- Compact size complete with oversized drip hood and padlockable doors, complete with 3 point padlockable stainless steel handle and 4" snow kick
- Acceptable for bottom entry. Mounting flange turned in all around for aesthetics and durability.



* Shown in optional ASA 61 grey



- Main fused section is service entrance rated complete with lockable doors and neutral/bonding facility
- CT section has rear CT/PT mounting pan and has hinged sealable and padlockable cover
- Deluxe Parks Green powder paint finish*
- Safety soft machine formed corners on doors and hood
- Standard size is 250-1200A, single or three phase, to 600V
- CSA certified assembly

NOTE

- Consult factory for various options available
- Utility meter socket, line side terminal box and TV/Telephone cell optional

For more information visit acdandy.com or call 1.800.642.2952