



22-01

designed to make your standard panel weatherproof



WEATHERPROOF LOAD CENTER ENCLOSURE Model #S-DLCR

- EEMAC 3R empty enclosure
- Multiple use enclosure specifically designed to house customer's load centers in locations where vandal and weatherproof protection is required
- Suitable for outdoor use to mount panel inside
- Protects against rain, sleet and snow
- Galvanized steel construction for body, door and backpan - code gauge
- Full length piano hinge type gasketed door with safety soft, machine formed corners
- Clasps on door with one padlockable type
- Punch raised rear mounting dimples
- Open bottom with inner flange
- Designed for easy cable wiring and entry

Options

- ASA 61Grey powder paint finish door only
- Siemens single or three phase panels
- Factory mounted model #DHTR-X heater/thermostat

Model #	Dimensions H x W x D (")	Bottom Opening Size	Non-Locking Clasp	Locking Clasp	Weight (lbs)
S-DLCR-10-8-4-HH	10.75 x 8 x 4.75	3.5 x 6.75	0	1	12
S-DLCR-14-9-4-HH	14.5 x 9 x 4.75	3.5 x 7.75	0	1	14
S-DLCR-30-18-6-HH	30 x 18 x 6	16.25 x 3.75	0	1	49
S-DLCR-40-18-6-HH	40 x 18 x 6	16.25 x 3.75	1	1	64
S-DLCR-46-18-6-HH	46 x 18 x 6	16.25 x 3.75	1	1	103
S-DLCR-60-18-6-HH	60 x 18 x 6	16.25 x 3.75	2	1	130